

ZH507

Compact high brightness laser projector









- Bright Full HD 1080p DuraCore laser projector -5500 lumens
- Versatile 1.6x zoom, vertical lens shift, portrait mode
- Ultimate control Crestron, Extron, AMX, PJ-Link and Telnet LAN commands
- Long lifetime and high reliability 30,000 hours of virtually maintenance-free operation



The ZH507 projector offers true convenience with low maintenance and longer-life laser technology in a small and lightweight chassis. It also features 4K and HDR compatibility and an impressive 5500 lumens.

Specifications

UPC: 796435 44 594 2, EAN: 5055387665996, Colour: White

Display/image Display technology

DL P™

Resolution 1080p Full HD (1920x1080)

Brightness 5,500 lumens Contrast ratio 300.000:1 Native aspect ratio 16:9 Aspect ratio - compatible 4:3 +/-30° Keystone correction horizontal Keystone correction - vertical +/-30°

Has vertical auto keystone correction

Displayable colors (millions) 1073.4

Horizontal scan rate 15.375 ~ 91.146 Khz 50 ~ 85 Hz (120Hz for 3D)Hz Vertical scan rate

Yes

Laser 30,000 hours

Uniformity 80%

Screen size 20.2" ~ 320.4" diagonal

Light source type LASER life Optical

Lamp info

Throw ratio 1.4:1 ~ 2.24:1 39.37" - 393.7" Projection distance Zoom 1.6 Zoom type Manual

Focal length (mm) 20.91mm~32.62mm/0.823"~1.284"

Lens shift Vertical +16% Native offset

Lens shift Yes - {{downloads_link}}

Connectivity

Connections Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA

(YPbPr/RGB), 2 x Audio 3.5mm, 1 x Mic 3.5mm, 1 x

Composite video

Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x micro USB

service, 1 x 3D sync

General

3D compatibility

Noise level (typical) 30dB Noise level (max) 32dB

PC compatibility UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p. 576i/p.

720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

IP rating IP6X

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Remote control Data remote with mouse function 918BTU/hour Heat dissipation

Speaker count Watts per speaker 10W In the box AC power cord

Remote control 2x AAA batteries

Input lag

Optional wireless models UHDCast Pro, QuickCast Bundle, QuickCast starter kit

282W

Networking LAN - control

Power

100V ~ 240V, 50-60Hz Power supply Power consumption (standby) <0.5W 227W Power consumption (min)

Power consumption (max) Weight and dimensions

13.27" x 10.43" x 4.82" Dimensions (W x D x H) 14.55 lbs Gross weight

Net weight 9.92 lbs





